



Force Sensor 1004 300g/C3

Item number: 3188



Technical Drawing



Technical Data

Basic Data		Unit
Type	Wägezelle	
Force direction	Compression	
Rated force Fx	300	g
Rated displacement	0.35	mm
Material	aluminum-alloy	
Dimensions	110mm x 10mm x 33mm	
Breaking force	300	%Fs
Variants	300g... 600g	

Electrical Data		Unit
Input resistance	415	Ohm
Tolerance input resistance	20	Ohm
Output resistance	350	Ohm
Tolerance output resistance	3	Ohm
Insulation resistance	2	GOhm
Rated range of excitation voltage from	2.5	V
Rated range of excitation voltage to	5	V
Operating range of excitation voltage from	1	V
Operating range of excitation voltage to	10	V
Zero signal	10	%Fs
Rated output	0.9	mV/V
relative error of characteristic value	0.1	mV/V

Accuracy Data		Unit
---------------	--	------

OIML Accuracy Data		Unit
OIML accuracy class	C3	
Zero return, 30 min.	0.017	±% der aufgebrauchten Last
Total error (per OIML R60)	0.02	±% des Nennlast
Temperature effect on zero	0.004	±% S / °C
Temperature effect on output	0.001	±% S / °C
Environmental Data		Unit
Rated temperature range from	-10	°C
Rated temperature range to	40	°C
Operating temperature range from	-30	°C
Operating temperature range to	70	°C
Storage temperature range from	-30	°C
Storage temperature range to	70	°C
Environmental protection	IP66	

Abbreviation : RD: „Reading“; FS: „Full Scale“;1) The exact nominal sensitivity is indicated in the test report;2) Nominal output for LCS130 250kg is 0,1%.

Pin Assignment

Channel	Symbol	Description	Wire color	PIN
	+Us	positive bridge supply	green	
	-Us	negative bridge supply	black	
	+Ud	positive bridge output	red	
	-Ud	negative bridge output	white	

Shield- transparent.